



## Technical Specifications

### General

|                       |                    |
|-----------------------|--------------------|
| Driver                | : Constant Current |
| Input Voltage         | : 220-240Vac       |
| Operating Temperature | : -15°C~+50°C      |

### Light Source

|                        |                                  |
|------------------------|----------------------------------|
| Light Source           | : Nichia                         |
| CRI (Ra)               | : >80 (>90 On Request)           |
| LED Colour Temperature | : 2700K / 3000K / 4000K<br>5700K |

### Optical

|                        |                                     |
|------------------------|-------------------------------------|
| Efficiency             | : >90%                              |
| Tilt                   | : Fixed                             |
| Beam Angle             | : 12°, 20°, 34°, 48°, 60°           |
| Diffuser/Lens Material | : Polycarbonate                     |
| Secondary Reflector    | : Vacuum Metalized<br>Chrome Finish |
| UGR                    | : <12                               |

### Physical

|          |                                                                              |
|----------|------------------------------------------------------------------------------|
| Body     | : Extruded Aluminium<br>with Die-cast Endcaps                                |
| Mounting | : Surface / Pendant                                                          |
| Finish   | : RAL 9004 Signal black<br>RAL 9016 Traffic White<br>RAL 9007 Grey aluminium |

### Driver

|                  |            |
|------------------|------------|
| Power Supply     | : Integral |
| Power Factor     | : >0.90    |
| THD              | : <10%     |
| Surge Protection | : 3KV      |
| Efficiency       | : >85%     |



## Ordering Guide

### Pendant - Direct / Surface

| ID   | Wattage  | Dimension (mm) |
|------|----------|----------------|
| 3469 | Upto 20W | 612 x 36 x 75  |
| 3469 | Upto 40W | 1212 x 36 x 75 |
| 3469 | Upto 80W | 2412 x 36 x 75 |

### Pendant - Direct-Indirect

| ID   | Wattage        | Dimension (mm) |
|------|----------------|----------------|
| 3469 | Upto 20W & 8W  | 612 x 36 x 75  |
| 3469 | Upto 40W & 15W | 1212 x 36 x 75 |
| 3469 | Upto 80W & 30W | 2412 x 36 x 75 |