



RADHA KRISHNA TEMPLE, GOA

## Technical Specifications

### General

ID	: 4089 (Sym) / 4090 (Asy)
System Wattage	: 18W LED
Driver Integral	: Constant Current
Operating Voltage	: 100-277Vac
Operating Temperature	: -15°C~+50°C

### Physical

Body	: Die-cast Aluminium
Front Ring	: 316 Grade Stainless Steel
Diffuser	: Toughened Clear Glass T=8mm
Mounting Sleeve	: ABS - Black
Mounting	: Recess

### Light Source

Light Source	: NICHIA
CRI (Ra)	: ≥80 (≥90 On Request)
LED Colour Temperature	: 2700K / 3000K / 4000K / 5700K

### Driver

Power Supply	: Integral
Input Voltage	: 240Vac
Frequency	: 50-60 Hz
Power Factor	: ≥0.9
THD	: <10%
Surge Protection	: 2.5KV
Efficiency	: >85%

### Optical Performance




Colour Temperature	: 3000K
Luminous flux	: 1925 lm(Sym) / 1299 lm(Asy)
Beam Angle	: 25° (Sym) / 35° x 45°(Asy)





Symmetrical



Asymmetrical



## Light Distribution



**Note :** It is our constant endeavor to upgrade the performance of our products. For the latest technical information, IES files and product updates please refer to the website at [www.klite.in](http://www.klite.in)